



LEAD-ACID BATTERY

PRODUCT BROCHURE

TIANNENG BATTERY GROUP CO., LTD
TIANNENG INTERNATIONAL CO., LIMITED

+86-572-6058015

+86-572-6058015

info@tianneng.com

www.tiannengglobal.com

HQ Add:
18#Baoqiao Rd.Huaxi industry park.Changxing.
Zhejiang Province.China

INT HQ Add:
Block C.6/F shun shing plaza, 50 stanley
street, central, Hong Kong

in Tianneng Group Official

Tianneng Group Official (@GroupTianneng)

YouTube Tianneng Group



Website



Electronic brochure

www.tiannengglobal.com

About Us

Tianneng is a Global Leading New Energy Company committed to providing environmentally-friendly battery solutions for various industries worldwide since 1986.

Tianneng now has nearly 30,000 employees and more than 160 subsidiaries around the world. There are 18 production bases in 7 provinces in China and 2 oversea manufacturing center in Vietnam. Tianneng set up 7 R&D centers to constantly develop technology and keep innovation in the area of lead acid batteries, lithium batteries, hydrogen Fuel Cells, and Sodium-ion batteries.

Honor:

- Global Top 500 New Energy Enterprises — Rank 2
- China Top 500 Private Enterprises — Rank 27
- China Top 500 Enterprises — Rank 127
- China Top 100 Light Industry Enterprises — Rank 4

Main Business areas:

- Battery and system Solutions (Motive, SLI, Energy Storage)
- Battery Recycling Solutions (Lead Acid battery recycling, Lithium-ion battery recycling)



\$7.5 billion
2025 Annual Sales



A+H Listed
688819.SH/00819.HK



8000+
Patents



No. 2
Global Top 500 New Energy Enterprises

Milestone



Global Footprint

18

China Production Base

Tianneng has established 18 production bases in eight provinces including Zhejiang, Anhui, Jiangsu, Henan, Guizhou, Shandong, Jiangxi and Gansu.

2

Overseas Production Base

Vietnam

1

Overseas Warehouse

Nigeria

7

Overseas Offices (Established)

Netherlands, Indonesia, Vietnam, Türkiye, Thailand, Nigeria, Argentina

3


Overseas Offices (Under Construction)

Philippines, Dubai, Brazil

4

China Office


Beijing, Shanghai, Hangzhou, Shenzhen



Research & Development


Strong research and development strength

 <p>270+ Define industry standards</p>	 <p>8000+ Industry patents</p>	 <p>6 CNAS laboratories</p>
--	--	---




Material Upgrade

Green rare earth alloy, graphene, carbon fiber; Reduced plate grid corrosion and creep, enhanced conductivity and heat transfer, and increased discharge power; Longer life, wider operating temperature, and more power.




Ecological Design

3D model simulation, Large data simulation by finite element analysis. Simulation of current and potential distribution to optimize plate grid design; Better pole plates for longer battery life



Lead Carbon Technology

Negative carbon technology, Inhibiting irreversible sulfation of the negative electrode, reducing the softening of the active material, and maintaining a durable internal assembly pressure; Excellent PSoC usage performance, long cycle life, wider use temperature. Inhibit the irreversible sulfation of the negative electrode, reduce the softening of the active material, and maintain the internal lasting assembly pressure; Excellent PSoC performance, long cycle life, wider operating temperature, greater charge acceptance;



Leading-edge design and craftsmanship

Vacuum and paste, high temperature curing, fully impregnated direct connection structure and double-layer double-effect patented third electrode design, etc.;

More reliable battery structure, better battery performance;



Intelligent Manufacturing

Automatic Production

Tianneng has the first domestic motive battery with an automatic continuous casting, rolling, continuous punching, and continuous coating production demonstration line, the domestic first small-density battery with an intelligent automatic assembly demonstration production line, which the energy and lead consumption have been greatly reduced, equipment operators have been reduced by 9/10, productivity has been increased by 50%, material costs have been reduced by 10%, corrosion resistance of the plate grids has been effectively improved, and cycle life has been increased by 10%.

Intelligent Brain

Based on industrial Internet design, Tianneng combines information technology and the advanced manufacturing industry to create an enterprise-level industrial Internet that integrates industrial data collection, product digitization, manufacturing process digitization, edge computing, industrial big data, and industrial APP.






Application

- Moped
- E-scooter
- Electric Two-wheeler



Application

- Electric Tricycle
- Electric four-wheel
- Low-speed EV



Application

- Golf Cart
- Wheelchair
- Sweeper

Motive Battery Solution

We provides green motive battery solutions for mobilities and all kinds of deep-cycle battery applications, involved with commuting, sightseeing, distribution, sanitation, etc. Our motive battery driving force is strong, long range endurance, products have a number of national patent protection technology, widely used in the global market, is a reliable choice for short-haul travel.

Product Series

TNE Series

TNEH Series

TNEP Series

TNE Series

General Deep Cycle battery

TNE Series are specific designed and developed for deep cycle application. This series with a number of national patent technologies and the cycle life can reach 400-600 cycles at 100% DOD, it is highly suitable to cyclic application such as electrical bicycle/tricycle, Golf trolleys and golf cart , EV etc. TN Power's deep cycle motive batteries take more than 45% market share in China domestic motive battery market.

Product Appearance



PRODUCT FEATURE

- **400~600 Cycles @100%DOD**
- **↑10% Energy Density**
Patent Structure Design
- **0% Acid Stratification**
Nano Silicon Gel Electrolytes
- **↓50% Anti-corrosion**
Patent Rare-earth Alloy

CERTIFICATES



APPLICATION

- Electric Two-wheeler
- E-scooter
- Electric Tricycle
- Electric four-wheel
- Electric Motorcycle
- Key's Electric Bike
- Wheelchair
- Sweeper
- Low-speed EV
- Golf Cart

TNE (General Deep Cycle battery)

S/N	Model	Nominal Voltage (V)	Nominal Capacity C ₂ /C ₃ (Ah) 1.75Vpc/25°C	Nominal Capacity C ₅ (Ah) 1.75Vpc/25°C	Nominal Capacity C ₂₀ (Ah) 1.80Vpc/25°C	Dimension(mm) ±1%				Terminal
						L	W	H	TH	
1	TNE12-15	12	12.0(C ₂)	12.8	15	151	99	98	103	M5
		12	12.6(C ₂)	13.9	15	151	99	98	98	M5
2	TNE12-25	12	20.0(C ₂)	21.5	25	180	77	171	171	M5
		12	21.6(C ₂)	23.2	25	181	77	171	171	M5
3	TNE12-38	12	32.0(C ₃)	32.9	38	267	77	170	170	M5
		12	32.6(C ₃)	34.0	38	267	77	171	171	M5
4	TNE12-45L	12	38.0(C ₃)	39.8	45	222	105	175	175	M5
		12	40.6(C ₃)	41.8	45	222	106	173	173	M5
5	TNE12-52	12	45.0(C ₃)	46.8	52	224	120	175	175	M6
		12	46.6(C ₃)	47.7	52	224	120	175	175	M6
6	TNE12-58	12	52.0(C ₃)	53.5	58	224	135	175	175	M6
		12	52.6(C ₃)	54.0	58	224	135	175	175	M6
7	TNE12-65	12	58.0(C ₃)	58.5	65	224	150	175	175	M6
		12	58.6(C ₃)	60.3	65	224	150	175	175	M6
8	TNE6-245	6	190(C ₃)	204	245	243	188	275	275	M8
9	TNE6-250	6	200(C ₃)	213	250	260	180	270	275	M8
10	TNE6-270	6	231(C ₃)	245	290	260	180	275	275	M8
11	TNE8-180	8	150(C ₃)	158	182	260	180	275	275	M8
12	TNE8-190	8	155(C ₃)	164	190	260	180	275	275	M8
13	TNE12-66	12	60(C ₃)	62	66	260	150	180	180	M6
14	TNE12-75	12	60(C ₃)	64	75	262	165	170	170	M6
15	TNE12-90	12	75(C ₃)	80	90	259	170	210	210	M6
16	TNE12-100	12	80(C ₃)	85	100	260	168	210	210	M6
17	TNE12-125	12	100(C ₃)	106	125	330	171	216	216	M8
18	TNE12-150	12	120(C ₃)	128	150	407	171	240	240	M8
19	TNE12-175	12	140(C ₃)	149	175	339	172	281	281	M8
20	TNE12-190	12	150(C ₃)	160	190	480	170	236	236	M8
21	TNE12-230	12	180(C ₃)	200	230	532	207	220	226	M8

TNEH Series

Long Cycle Life Black Gold Battery

TNEH Series are specific designed and developed for long life deep cycle application. This series combined advanced carbon and graphene tech and its cycle life can reach 500-600 cycles at 100% DOD, it is highly suitable to cyclic application such as electrical bicycle/tricycle, Golf trolleys and golf cart , EV etc. TN Power's deep cycle motive batteries take more than 45% market share in China domestic motive battery market.


Product Appearance



PRODUCT FEATURE

- **↑20% Cycle Life**
500~600 Cycles @100%DOD
- **↑10% Discharge Power**
Positive Carbon Fieber
- **↑15% Low Temp. Performance**
Negative Graphene
- **↑50% Anti-corrosion**
Patent Rare-earth Alloy

CERTIFICATES



APPLICATION

- Electric Two-wheeler
- E-scooter
- Electric Tricycle
- Electric four-wheel
- Electric Motorcycle
- Key's Electric Bike
- Wheelchair
- Sweeper
- Low-speed EV
- Golf Cart

TNEH (Deep Cycle Black Gold Battery)

S/N	Model	Nominal Voltage (V)	Nominal Capacity C ₂ /C ₃ (Ah) 1.75Vpc/25°C	Nominal Capacity C ₅ (Ah) 1.75Vpc/25°C	Nominal Capacity C ₂₀ (Ah) 1.80Vpc/25°C	Dimension(mm) ±1%				Terminal
						L	W	H	TH	
1	TNEH12-15	12	13.2(C ₂)	13.7	15	151	99	98	104	M5
2	TNEH12-27	12	22.3(C ₂)	23.5	27	181	77	171	171	M5
3	TNEH12-40	12	35.5(C ₃)	36.5	40	267	77	171	171	M5

TNEP Series

Long Mileage Battery

TNEP Series are specific designed and developed for long life deep cycle application. This series with a number of national patent technologies and the cycle life can reach 500-600 cycles at 100% DOD, it is highly durable to cyclic application such as electrical bicycle/tricycle, golf cart, EV etc. TN Power's deep cycle motive batteries take more than 45% market share in China domestic motive battery market.


Product Appearance



PRODUCT FEATURE

- **↑110% Capacity Improved**
Special Active Formula
- **↑15% Discharge Power**
Positive Carbon Fieber
- **500~600 Cycles @100%DOD**
- **↑50% Anti-corrosion**
Patent Rare-earth Alloy

CERTIFICATES



APPLICATION

- Electric Two-wheeler
- E-scooter
- Electric Tricycle
- Electric four-wheel
- Electric Motorcycle
- Key's Electric Bike
- Wheelchair
- Sweeper
- Low-speed EV
- Golf Cart

TNEP (Deep Cycle Premium Battery)

S/N	Model	Nominal Voltage (V)	Nominal Capacity C ₂ /C ₃ (Ah) 1.75Vpc/25°C	Nominal Capacity C ₅ (Ah) 1.75Vpc/25°C	Nominal Capacity C ₂₀ (Ah) 1.80Vpc/25°C	Dimension(mm) ±1%				Terminal
						L	W	H	TH	
1	TNEP12-16	12	14(C ₂)	15	16	151	99	98	99	M5
2	TNEP12-28	12	23(C ₂)	24	28	181	77	170	170	M5
3	TNEP12-42	12	34(C ₃)	36	42	195	130	157.5	162	M5
4	TNEP12-50	12	41(C ₃)	43	50	198.5	166	174	174	M6
5	TNEP12-130	12	107(C ₃)	120	130	330	171	222	222	M8
6	TNEP6-240	6	187(C ₃)	200	240	260	180	245	251	M8
7	TNEP6-290	6	231(C ₃)	245	290	260	180	275	275	M8
8	TNEP6-310	6	260(C ₃)	280	310	353	180	270	270	M8
9	TNEP6-400	6	285(C ₃)	320	400	295	178	345	350	M8
10	TNEP6-420	6	330(C ₃)	380	420	295	178	405	409	M8

HIGH TEMPERATURE BATTERY

High temperature series battery is specially developed for tropical, subtropical and other temperature areas above 0°C. Based on the original TNE, TNEH and TNEP series, the series improves the life of the battery above 0°C through special design and adjustment, which is very suitable for cycle applications such as electric bicycles and electric two-wheelers.


Product Appearance



PRODUCT FEATURE

- **Rare earth alloy**
Patented formula alloy, reduce grid corrosion under high temp.
- **Optimal design**
Optimize plate design, extend life of positive plate
- **High strength case**
Special ABS material, more resistant to high temperature
- **↑10% cycle life**
Under high temperature condition

CERTIFICATES




APPLICATION

- Electric Two-wheeler
- E-scooter
- Electric Tricycle

HIGH TEMPERATURE BATTERY

S/N	Model	Nominal Voltage (V)	Nominal Capacity C2/C3(Ah) 1.75Vpc/25°C	Nominal Capacity C5 (Ah) 1.75Vpc/25°C	Nominal Capacity C20 (Ah) 1.80Vpc/25°C	Dimension (±3mm)				Terminal
						L	W	H	TH	
1	TNE12-15	12	12	12.8	15	151	99	98	103	I9
2	TNE12-25	12	20	21.5	25	180	77	171	171	I10
3	TNEH12-15	12	13.2	13.7	15	151	99	98	103	I9
4	TNEH12-27	12	22.3	23.5	27	181	77	171	171	I10



Application

- Electric Forklift
- Electric Four-wheels
- Sweeper
- Electric Tricycle
- Lift Truck

Traction Battery Solution

TIANNENG provides a wide range of power battery solutions for electric forklift and stacker, our products comply with DIN and BS standards, our products have a very good user experience, high stability, easy operation, low noise, no pollution, a large number of applications in warehousing, logistics, handling and other places, and have extensive cooperation with various car manufacturers.

Product Series

PzB Series

PzS Series

PzB Series

BS Standard Forklift Battery

PZB Series forklift battery provides is consistent with BS standard, its cycle life could reach 1500 cycles @80%DOD. The series boaste a high level of power and reliability for industrial traction application.

Product Appearance



PRODUCT FEATURE

- Comply with BS standards;
- Longer service life, Up to 1500 cycles @80%DOD;
- Less water loss, Less maintenance;
- Perfect soft connection, easy to install.

CERTIFICATES



APPLICATION

- Electric Forklift
- Sweeper
- Electric Tricycle
- Electric Four-wheels
- Lift Truck

PzB (Traction Battery BS Series)

S/N	Model	Nominal Voltage (V)	Nominal Capacity C5 (Ah) <small>1.75Vpc/30°C</small>	Dimension (±2mm)			
				L	W	H	TH
1	2PzB100	2	100	45	158	389	421
2	3PzB150	2	150	61	158	389	421
3	4PzB200	2	200	77	158	389	421
4	5PzB250	2	250	93	158	389	421
5	6PzB300	2	300	109	158	389	421
6	7PzB350	2	350	125	158	389	421
7	8PzB400	2	400	141	158	389	421
8	9PzB450	2	450	157	158	389	421
9	10PzB500	2	500	173	158	389	421
10	2PzB110	2	110	45	158	405	437
11	3PzB165	2	165	61	158	405	437

PzB (Traction Battery BS Series)							
S/N	Model	Nominal Voltage (V)	Nominal Capacity C5 (Ah) 1.75Vpc/30°C	Dimension (±2mm)			
				L	W	H	TH
12	4PzB220	2	220	77	158	405	437
13	5PzB275	2	275	93	158	405	437
14	6PzB330	2	330	109	158	405	437
15	7PzB385	2	385	125	158	405	437
16	8PzB440	2	440	141	158	405	437
17	9PzB495	2	495	157	158	405	437
18	10PzB550	2	550	173	158	405	437
19	2PzB120	2	120	45	158	405	437
20	3PzB180	2	180	61	158	405	437
21	4PzB240	2	240	77	158	405	437
22	5PzB300	2	300	93	158	405	437
23	6PzB360	2	360	109	158	405	437
24	7PzB420	2	420	125	158	405	437
25	8PzB480	2	480	141	158	405	437
26	9PzB540	2	540	157	158	405	437
27	10PzB600	2	600	173	158	405	437
28	2PzB130	2	130	45	158	451	483
29	3PzB195	2	195	61	158	451	483
30	4PzB260	2	260	77	158	451	483
31	5PzB325	2	325	93	158	451	483
32	6PzB390	2	390	109	158	451	483
33	7PzB455	2	455	125	158	451	483

PzB (Traction Battery BS Series)							
S/N	Model	Nominal Voltage (V)	Nominal Capacity C5 (Ah) 1.75Vpc/30°C	Dimension (±2mm)			
				L	W	H	TH
34	8PzB520	2	520	141	158	451	483
35	9PzB585	2	585	157	158	451	483
36	10PzB650	2	650	173	158	451	483
37	2PzB140	2	140	45	158	480	512
38	3PzB210	2	210	61	158	480	512
39	4PzB280	2	280	77	158	480	512
40	5PzB350	2	350	93	158	480	512
41	6PzB420	2	420	109	158	480	512
42	7PzB490	2	490	125	158	480	512
43	8PzB560	2	560	141	158	480	512
44	9PzB630	2	630	157	158	480	512
45	10PzB700	2	700	173	158	480	512
46	2PzB150	2	150	45	158	506	538
47	3PzB225	2	225	61	158	506	538
48	4PzB300	2	300	77	158	506	538
49	5PzB375	2	375	89	158	506	538
50	6PzB450	2	450	109	158	506	538
51	7PzB525	2	525	125	158	506	538
52	8PzB600	2	600	141	158	506	538
53	9PzB675	2	675	157	158	506	538
54	10PzB750	2	750	173	158	506	538
55	2PzB160	2	160	45	158	531	563

PzB (Traction Battery BS Series)							
S/N	Model	Nominal Voltage (V)	Nominal Capacity C5 (Ah) 1.75Vpc/30°C	Dimension (±2mm)			
				L	W	H	TH
56	3PzB240	2	240	61	158	506	538
57	4PzB320	2	320	77	158	506	538
58	5PzB400	2	400	93	158	506	538
59	6PzB480	2	480	109	158	506	538
60	7PzB560	2	560	125	158	506	538
61	8PzB640	2	640	141	158	506	538
62	9PzB720	2	720	157	158	506	538
63	10PzB800	2	800	173	158	506	538
64	2PzB180	2	180	45	158	548	580
65	3PzB270	2	270	61	158	548	580
66	4PzB360	2	360	77	158	548	580
67	5PzB450	2	450	89	158	548	580
68	6PzB540	2	540	109	158	548	580
69	7PzB630	2	630	125	158	548	580
70	8PzB720	2	720	141	158	548	580
71	9PzB810	2	810	157	158	548	580
72	10PzB900	2	900	173	158	548	580
73	2PzB200	2	200	45	158	615	647
74	3PzB300	2	300	61	158	625	657
75	4PzB400	2	400	77	158	625	657
76	5PzB500	2	500	93	158	625	657
77	6PzB600	2	600	109	158	625	657

PzB (Traction Battery BS Series)							
S/N	Model	Nominal Voltage (V)	Nominal Capacity C5 (Ah) 1.75Vpc/30°C	Dimension (±2mm)			
				L	W	H	TH
78	7PzB700	2	700	125	158	625	657
79	8PzB800	2	800	141	158	625	657
80	9PzB900	2	900	157	158	625	657
81	10PzB1000	2	1000	173	158	625	657
82	2PzB210	2	210	45	158	685	717
83	3PzB315	2	315	61	158	685	717
84	4PzB420	2	420	77	158	685	717
85	5PzB525	2	525	93	158	685	717
86	6PzB630	2	630	109	158	685	717
87	7PzB735	2	735	125	158	685	717
88	8PzB840	2	840	141	158	685	717
89	9PzB945	2	945	157	158	685	717
90	10PzB1050	2	1050	173	158	685	717
91	2PzB220	2	220	45	158	685	717
92	3PzB330	2	330	61	158	685	717
93	4PzB440	2	440	77	158	685	717
94	5PzB550	2	550	93	158	685	717
95	6PzB660	2	660	109	158	685	717
96	7PzB770	2	770	125	158	685	717
97	8PzB880	2	880	141	158	685	717
98	9PzB990	2	990	157	158	685	717
99	10PzB1100	2	1100	173	158	685	717

PzS Series

DIN Standard Forklift Battery

PZS Series forklift battery provides is consistent with DIN standard, its cycle life could reach 1500 cycles @80%DOD. The series boaste a high level of power and reliability for industrial traction application.

Product Appearance



PRODUCT FEATURE

- Comply with DIN standards;
- Longer service life, Up to 1500 cycles @80%DOD;
- Less water loss, Less maintenance;
- Perfect soft connection, easy to install.

CERTIFICATES



APPLICATION

- Electric Forklift
- Sweeper
- Electric Tricycle
- Electric Four-wheels
- Lift Truck

PzS (Traction Battery DIN Series)

S/N	Model	Nominal Voltage (V)	Nominal Capacity C5 (Ah) <small>1.70Vpc/30°C</small>	Dimension (±2mm)			
				L	W	H	TH
1	2PzS120	2	120	47	198	323	355
2	3PzS180	2	180	65	198	313	355
3	4PzS240	2	240	83	198	323	355
4	5PzS300	2	300	101	198	313	355
5	6PzS360	2	360	119	198	323	355
6	7PzS420	2	420	137	198	313	355
7	8PzS480	2	480	155	198	323	355
8	9PzS540	2	540	174	198	323	355
9	10PzS600	2	600	192	198	323	355
10	2PzS140	2	140	47	198	380	412

PzS (Traction Battery DIN Series)							
S/N	Model	Nominal Voltage (V)	Nominal Capacity C5 (Ah) 1.70Vpc/30°C	Dimension (±2mm)			
				L	W	H	TH
11	3PzS210	2	210	65	198	380	412
12	4PzS280	2	280	83	198	380	412
13	5PzS350	2	350	101	198	380	412
14	6PzS420	2	420	119	198	380	412
15	7PzS490	2	490	137	198	380	412
16	8PzS560	2	560	155	198	380	412
17	9PzS630	2	630	174	198	380	412
18	10PzS700	2	700	192	198	380	412
19	2PzS160	2	160	47	198	403	435
20	3PzS240	2	240	65	198	403	435
21	4PzS320	2	320	83	198	403	435
22	5PzS400	2	400	101	198	403	435
23	6PzS480	2	480	119	198	403	435
24	7PzS560	2	560	137	198	403	435
25	8PzS640	2	640	155	198	403	435
26	9PzS720	2	720	174	198	403	435
27	10PzS800	2	800	192	198	403	435
28	2PzS180	2	180	47	198	473	505
29	3PzS270	2	270	65	198	473	505
30	4PzS360	2	360	83	198	473	505

PzS (Traction Battery DIN Series)							
S/N	Model	Nominal Voltage (V)	Nominal Capacity C5 (Ah) 1.70Vpc/30°C	Dimension (±2mm)			
				L	W	H	TH
31	5PzS450	2	450	101	198	473	505
32	6PzS540	2	540	119	198	473	505
33	7PzS630	2	630	137	198	473	505
34	8PzS720	2	720	155	198	473	505
35	9PzS810	2	810	174	198	473	505
36	10PzS900	2	900	192	198	473	505
37	2PzS210	2	210	47	198	513	545
38	3PzS315	2	315	65	198	513	545
39	4PzS420	2	420	83	198	513	545
40	5PzS525	2	525	101	198	513	545
41	6PzS630	2	630	119	198	513	545
42	7PzS735	2	735	137	198	513	545
43	8PzS840	2	840	155	198	513	545
44	9PzS945	2	945	174	198	513	545
45	10PzS1050	2	1050	192	198	513	545
46	2PzS230	2	230	47	198	548	580
47	3PzS345	2	345	65	198	548	580
48	4PzS460	2	460	83	198	548	580
49	5PzS575	2	575	101	198	548	580
50	6PzS690	2	690	119	198	548	580

PzS (Traction Battery DIN Series)							
S/N	Model	Nominal Voltage (V)	Nominal Capacity C5 (Ah) 1.70Vpc/30°C	Dimension (±2mm)			
				L	W	H	TH
51	7PzS805	2	805	137	198	548	580
52	8PzS920	2	920	155	198	548	580
53	9PzS1035	2	1035	174	198	548	580
54	10PzS1150	2	1150	192	198	548	580
55	2PzS240	2	240	47	198	576	608
56	3PzS360	2	360	65	198	576	608
57	4PzS480	2	480	83	198	576	608
58	5PzS600	2	600	101	198	576	608
59	6PzS720	2	720	119	198	576	608
60	7PzS840	2	840	137	198	576	608
61	8PzS960	2	960	155	198	576	608
62	9PzS1080	2	1080	174	198	576	608
63	10PzS1200	2	1200	192	198	576	608
64	2PzS250	2	250	47	198	576	608
65	3PzS375	2	375	65	198	576	608
66	4PzS500	2	500	83	198	576	608
67	5PzS625	2	625	101	198	576	608
68	6PzS750	2	750	119	198	576	608
69	7PzS875	2	875	137	198	576	608
70	8PzS1000	2	1000	155	198	576	608
71	9PzS1125	2	1125	174	198	576	608
72	10PzS1250	2	1250	192	198	576	608
73	2PzS280	2	280	47	198	680	712
74	3PzS420	2	420	65	198	680	712
75	4PzS560	2	560	83	198	680	712

PzS (Traction Battery DIN Series)							
S/N	Model	Nominal Voltage (V)	Nominal Capacity C5 (Ah) 1.70Vpc/30°C	Dimension (±2mm)			
				L	W	H	TH
76	5PzS700	2	700	101	198	680	712
77	6PzS840	2	840	119	198	680	712
78	7PzS980	2	980	137	198	680	712
79	8PzS1120	2	1120	155	198	680	712
80	9PzS1260	2	1260	174	198	680	712
81	10PzS1400	2	1400	192	198	680	712
82	2PzS300	2	300	47	198	680	712
83	3PzS450	2	450	65	198	680	712
84	4PzS600	2	600	83	198	680	712
85	5PzS750	2	750	101	198	680	712
86	6PzS900	2	900	119	198	680	712
87	7PzS1050	2	1050	137	198	680	712
88	8PzS1200	2	1200	155	198	680	712
89	9PzS1350	2	1350	174	198	680	712
90	10PzS1500	2	1500	192	198	680	712
91	2PzS310	2	310	47	198	723	755
92	3PzS465	2	465	65	198	723	755
93	4PzS620	2	620	83	198	723	755
94	5PzS775	2	775	101	198	723	755
95	6PzS930	2	930	119	198	723	755
96	7PzS1085	2	1085	137	198	723	755
97	8PzS1240	2	1240	155	198	723	755
98	9PzS1395	2	1395	174	198	723	755
99	10PzS1550	2	1550	192	198	723	755



Application

- Residential
- Solar Energy
- Other renewable energy



Application

- UPS/EPS
- Telecommunication
- Electric Power



Application

- Alarm&safety System
- Signal
- Monitor

Reserve/Energy Storage Solution

Tianneng provides solutions for energy storage, reserve and other industrial scenarios, with excellent product cycle performance, stability and reliability, to provide customers with solid green energy guarantee.

Product Series

TN Series

TNX Series

TNF Series

TNG Series

TNC Series

TN Series

General Purpose AGM Battery

TN series is a general-purpose valveregulate lead-acid (VRLA) AGM battery that combines the TN Group's industry scale and advanced equipment to offer highly reliable products at the most competitive prices. With a design service life of 15 years (2V), 12 years (\geq 38Ah @ 12V), and 5 years (< 38Ah @ 12V) for this series, the series has excellent cycling performance and is ideal for a variety of applications in reserve and cycling.

Product Appearance



PRODUCT FEATURE

- **100% Model Coverage**
Both Float & Cycle Application
- **>98% 28d Capacity Retention**
High Purity Electrolyte
- **120% Charging Acceptance**
Special Negative Additive
- **150% Anti-corrosion**
Patent Rare-earth Alloy

CERTIFICATES



APPLICATION

- Residential
- Solar Energy
- Wind Energy
- UPS/EPS
- Telecommunication
- Electric Power
- Alarm & safety System
- Signal
- Monitor

TN (GENERAL PURPOSE AGM BATTERY)

S/N	Model	Nominal Voltage (V)	Nominal capacity 1.80V/cell(Ah)	Dimension(mm) \pm 1%				Weight (Kg) \pm 3%	Terminal
				L	W	H	TH		
1	TN12-4.5	12	4.5(C ₂₀)	90	70	101	107	1.42	T1/T2
2	TN12-5.0	12	5.0(C ₂₀)	90	70	101	107	1.45	T1/T2
3	TN12-5.5	12	5.5(C ₂₀)	90	70	101	107	1.59	T1/T2
4	TN12-7.0	12	7.0(C ₂₀)	151	65	94	100	2.00	T1/T2
5	TN12-7.5	12	7.5(C ₂₀)	151	65	94	100	2.08	T1/T2
6	TN12-9.0	12	9.0(C ₂₀)	151	65	94	100	2.45	T1/T2
7	TN12-12	12	12(C ₂₀)	151	98	94	100	3.29	T1/T2
8	TN12-17	12	17(C ₂₀)	181.4	76.5	166.5	166.5	4.80	M5/F3
9	TN12-18	12	18(C ₂₀)	181.4	76.5	166.5	166.5	5.40	M5/F3
10	TN12-20	12	20(C ₂₀)	181.4	76.5	166.5	166.5	5.70	M5/F3
11	TN12-24	12	24(C ₂₀)	167	177	125	125	7.20	M5
12	TN12-26	12	26(C ₂₀)	167	177	125	125	8.20	M5
13	TN12-28	12	28(C ₂₀)	167	177	125	125	8.70	M5

TN (GENERAL PURPOSE AGM BATTERY)									
S/N	Model	Nominal Voltage (V)	Nominal capacity 1.80V/cell(Ah)	Dimension(mm) ±1%				Weight (Kg)±3%	Terminal
				L	W	H	TH		
14	TN12-33	12	33(C ₂₀)	195	130	158	166.2	9.5	M6
15	TN12-38	12	38(C ₁₀)	197	166	168.5	168.5	11.8	M6
16	TN12-50	12	50(C ₁₀)	198	166	169	169	13.7	M6
17	TN12-55	12	55(C ₁₀)	229	138	208	214	16.7	M6
18	TN12-65	12	65(C ₁₀)	348	167	177	177	19.2	M6
19	TN12-70	12	70(C ₁₀)	348	167	177	177	21.4	M6
20	TN12-80	12	80(C ₁₀)	260	168	211	217	21.8	M6
21	TN12-100	12	100(C ₁₀)	330	173	213.5	220.5	28.0	M8
22	TN12-120	12	120(C ₁₀)	408	177	224	224	35.0	M8
23	TN12-150	12	150(C ₁₀)	483	170	239.5	239.5	42.0	M8
24	TN12-200	12	200(C ₁₀)	522	239	218	224	60.0	M8
25	TN12-220	12	220(C ₁₀)	522	239	218	224	61.5	M8
26	TN12-250	12	250(C ₁₀)	522	268	220	226	69.7	M8

TN (GENERAL PURPOSE AGM BATTERY)									
S/N	Model	Nominal Voltage (V)	Nominal capacity 1.80V/cell(Ah)	Dimension(mm) ±1%				Weight (Kg)±3%	Terminal
				L	W	H	TH		
27	TN2-100	2	100(C ₁₀)	171	72	205	211	5.6	M8
28	TN2-200	2	200(C ₁₀)	172	110	329	350	12.7	M8
29	TN2-300	2	300(C ₁₀)	171	150	329	351	17.8	M8
30	TN2-400	2	400(C ₁₀)	211	176	329	351	24.4	M8
31	TN2-500	2	500(C ₁₀)	242	172	329	351	29.0	M8
32	TN2-600	2	600(C ₁₀)	301	176	330	351	36.0	M8
33	TN2-800	2	800(C ₁₀)	410	176	330	365	48.5	M8
34	TN2-1000	2	1000(C ₁₀)	475	174	328	349	58.8	M8
35	TN2-1200	2	1200(C ₁₀)	475	174	328	349	64.1	M8
36	TN2-1300	2	1300(C ₁₀)	400	350	342	364	85.0	M8
37	TN2-1500	2	1500(C ₁₀)	400	350	342	364	94.5	M8
38	TN2-2000	2	2000(C ₁₀)	491	351	342	368	120	M8
39	TN2-3000	2	3000(C ₁₀)	710	351	342	368	178.5	M8

TNX Series

Standby high-power battery

TNX series is a product specifically developed to meet high-rate discharge requirements. It adopts a high-current discharge design, with a discharge output power 10-15% higher than that of ordinary batteries within 15 minutes. This can effectively reduce the number of batteries used and the initial investment in the project, and can be widely applied in scenarios such as data centers and UPS systems.

Product Appearance



PRODUCT FEATURE

- 15min high-rate design
- AGM technology
- High specific energy plates
- Strict process, good consistency

CERTIFICATES



APPLICATION

- IDC/AIDC
- UPS
- EPS
- Telecom

TNX (Standby high-power battery)

S/N	Model	Nominal Voltage (V)	Nominal capacity 1.80V/cell(Ah)	Rated Power 15min-1.67V(w/cell)	Dimension(mm) ±1%				Weight (Kg)±3%	Terminal
					L	W	H	TH		
1	TN12-28W	12	7.5(C20)	28	151	65	94	100	2.08	T2
2	TN12-36W	12	9.0(C20)	36	151	65	94	100	2.45	T2
3	TN12-240W	12	70(C10)	240	348.4	167	177	177	21.4	M6
4	TN12-342W	12	100(C10)	342	330	173	213.5	220.5	29.0	M8
5	TN12-390W	12	105(C10)	390	330	173	213.5	220.5	31.8	M8
6	TN12-510W	12	150(C10)	510	483	170	239.5	239.5	42.0	M8
7	TN12-550W	12	145(C10)	550	483	170	239.5	239.5	44.5	M8
8	TN12-650W	12	185(C10)	650	532	207	214	220	56.0	M8
9	TN12-700W	12	205(C10)	700	532	207	214	220	59.0	M8
10	TN12-700W	12	220(C10)	700	522	239	218	224	61.5	M8
11	TN12-765W	12	225(C10)	765	522	239	218	224	64.0	M8
12	TN12-800W	12	228(C10)	800	522	239	218	224	66.0	M8
13	TN12-820W	12	250(C10)	820	522	268	220	226	72.2	M8
14	TN12-850W	12	260(C10)	850	522	268	220	226	75.4	M8
15	TN12-1000W	12	280(C10)	850	522	268	220	226	82.0	M8

TNF Series

Front terminal valve-regulated lead acid battery

TNF front terminal battery combines high energy density with installation space requirements. It is specially designed for communication and power applications. The positive and negative terminals of the battery adopt a front-mounted design, making battery loading and unloading very convenient. It is suitable for 19 and 23-inch standard cabinets. It is widely used in various fields such as telecommunications, UPS power supplies, substations, control systems, microwave relay stations, and wind and solar energy storage.

Product Appearance



PRODUCT FEATURE

- **Front, terminal, facilitating installation and maintenance;**
- **Narrow and elongated shape, suitable for 19/23-inch standard cabinets;**
- **Centralized exhaust design, safe and environmentally friendly;**
- **Designed floating life: 12 years**

CERTIFICATES



APPLICATION

- Telecommunication
- Electric Power
- Data Centers
- Energy Storage

TNF (Front terminal valve-regulated lead acid battery)

S/N	Model	Nominal Voltage (V)	Nominal Capacity C ₁₀ (Ah) 1.80Vpc/25°C	Dimension(mm) ±1%				Weight (kg) ±3%	Terminal
				L	W	H	TH		
1	TNF12-55	12	55	277	106	223	223	17.0	M6
2	TNF12-100	12	100	394	109.5	286.5	286.5	30.5	M6
3	TNF12-150	12	150	551	110	285	285	44.5	M6
4	TNF12-190	12	190	560	125	317	317	57.5	M8
5	TNF12-200	12	200	560	125	317	317	59.0	M8

TNG Series

General Purpose GEL Battery

TNG series adopts the patented nano-gel electrolyte technology. The series offers over 15 years design life, and it has extremely high deep-cycle recovery capability. It is highly suitable for outdoor applications in the telecommunications sector, renewable energy systems, and other harsh environmental applications.

Product Appearance



PRODUCT FEATURE

- **GEL Technology**
- **↑20% Cycle Life**
260~300 Cycle Times
- **↑10% Low Temp Capacity**
Nano Gel Electrolyte
- **↑20% Charge Acceptance**
Special Negative Additive

CERTIFICATES



APPLICATION

- Residential
- Solar Energy
- Wind Energy
- UPS/EPS
- Telecommunication
- Electric Power
- Alarm&safety System
- Signal
- Monitor

TNG (General Purpose GEL Battery)

S/N	Model	Nominal Voltage (V)	Nominal capacity 1.80V/cell(Ah)	Dimension(mm) ±1%				Weight (Kg)±3%	Terminal
				L	W	H	TH		
1	TNG12-38	12	38	197	166	168.5	168.5	12.3	M6
2	TNG12-50	12	50	198	166	169	169	13.7	M6
3	TNG12-65	12	65	348.4	167	177	177	19.8	M6
4	TNG12-90	12	90	306.5	168	211	217	29.0	M6
5	TNG12-100	12	100	330	173	213.5	220.5	29.6	M8
6	TNG12-120	12	120	408	177	224	224	34.9	M8
7	TNG12-150	12	150	483	170	239.5	239.5	44.0	M8
8	TNG12-200	12	200	522	239	218	224	60.1	M8
9	TNG12-250B	12	250	522	268	220	226	72.5	M8
10	TNG2-100	2	100	171	72	205	211	5.6	M8
11	TNG2-200	2	200	172	110	329	350	13.0	M8
12	TNG2-300	2	300	171	150	329	351	17.8	M8
13	TNG2-500	2	500	242	172	329	351	29.0	M8
14	TNG2-600	2	600	301	176	330	351	36.0	M8
15	TNG2-1000	2	1000	475	174	328	349	58.8	M8

TNC Series

Lead Carbon (Pb-C) Battery

TNC series adopts newest lead carbon technology which add carbon material into negative electrode to slow down the sulfation. The TNC series battery provides not only high energy density, but also high power, rapid charge and discharge, longer cycle life. It's very suitable for renewable energy storage or where commercial power is unstable.

Product Appearance



PRODUCT FEATURE

- Lead carbon Technology
- 60%DOD2500(12V);3500(2V)
- Multi-element Patent Rare Earth Alloy
- HRPSoC Technology

CERTIFICATES



APPLICATION

- Residential
- Solar Energy
- Wind Energy
- UPS/EPS
- Telecommunication
- Electric Power
- Alarm&safety System
- Signal
- Monitor

TNC (LEAD CARBON (Pb-C) BATTERY)

S/N	Model	Nominal Voltage (V)	Nominal capacity 1.80V/cell(Ah)	Dimension(mm) ±1%				Weight (Kg)±3%	Terminal
				L	W	H	TH		
1	TNC12-65	12	65	260	168	211	217	24.5	F16
2	TNC12-80P	12	80	330	173	213.5	220.5	30.5	F20
3	TNC12-100	12	100	408	177	224	224	35.5	F20
4	TNC12-150	12	150	532	207	214	220	55.0	F20
5	TNC12-170	12	170	522	239	218	224	63.0	F20
6	TNC12-200	12	200	522	268	220	226	73.0	F20
7	TNC2-1000	2	1000	475	174	328	349	64.0	F20



Starter Battery Solution

TIANNENG provides starter battery solutions for passenger cars. The battery manufacturing strictly follows multiple standards such as JIS, DIN and SCI, and combines EFB and AGM technologies for excellent capacity performance, energy saving and consumption reduction, making the environment greener and life healthier.

Product Series

- TA Series
- TAS Series
- TAA Series

TA Series

General Starter Battery

TA Series keeps consistent with JIS, SCI, DIN and EN standards with super cranking power which ensures dependable start in cold weather, excellent corrosion-resistance performance in high temperature condition and great vibration resistance. The Series has longer life and lower internal resistance, is highly suited for cars, trucks, tractor and the starter for other vehicles as automobile battery.

Product Appearance



PRODUCT FEATURE

- SLA battery, Maintenance Free
- Stronger Starting Capacity
- Excellent Charging Acceptance
- Excellent Vibration Resistance

CERTIFICATES



APPLICATION

- Car starting
- Ship starting
- Oiler starting

STARTER BATTERY-C SERIES

S/N	Model	International Model	International Standard	Nominal Voltage (V)	RC (min)	CCA/-18°C (A)	Dimension(mm)				Weight(kg)	Terminal	Layout
							L	W	H	TH			
1	55D23LX TA-C	55D23	JIS	12	82	485	232	173	204	225	14.1±1.0	T2	L
2	55D23RX TA-C	55D23	JIS	12	82	485	232	173	204	225	14.1±1.0	T2	R
3	55D26LX TA-C	55D26	JIS	12	88	485	260	173	204	225	15.3±1.0	T2	L
4	55D26RX TA-C	55D26	JIS	12	88	485	260	173	204	225	15.3±1.0	T2	R
5	80D26LX TA-C	80D26	JIS	12	100	500	260	173	204	225	16.5±1.0	T2	L
6	80D26RX TA-C	80D26	JIS	12	100	500	260	173	204	225	16.5±1.0	T2	R
7	95D31LX TA-C	95D31	JIS	12	140	630	306	173	204	225	19.4±1.0	T2	L
8	95D31RX TA-C	95D31	JIS	12	140	630	306	173	204	225	19.4±1.0	T2	R
9	105E41R TA-C	105E41	JIS	12	180	700	408	173	205	226	24.8±1.0	T2	R
10	105E41RB TA-C	105E41	JIS	12	180	700	408	173	205	234	24.8±1.0	B	R
11	58500 TA-C	58500	SAE	12	65	370	250	174	158	177	11.8±1.0	T2	R
12	85610 TA-C	85610	SAE	12	90	470	230	173	181	203	14±1.0	T2	L
13	86610 TA-C	86610	SAE	12	90	470	230	173	181	203	14±1.0	T2	R
14	L2-400 TA-C	L2-400	EN	12	85	485	242	175	190	190	14.1±1.0	T2	L
15	L2-400R TA-C	L2-400	EN	12	85	485	242	175	190	190	14.1±1.0	T2	R
16	T6 TA-C	T6	EN	12	100	525	278	175	175	175	15.5±1.0	T2	L
17	N150R TA-C	N150	JIS	12	240	800	510	216	194	217	35.8±1.0	T2	R
18	N150RB TA-C	N150	JIS	12	240	800	510	216	194	229	36±1.0	B	R

STARTER BATTERY-S SERIES													
S/N	Model	International Model	International Standard	Nominal Voltage (V)	Nominal Capacity (Ah)	CCA/-18°C (A)	Dimension				Weight(kg)	Terminal	Layout
							L	W	H	TH			
1	38B20L TA-S	38B20	JIS	12	36	325	197	129	203	227	10.1±0.5	T1	L
2	38B20R TA-S	38B20	JIS	12	36	325	197	129	203	227	10.1±0.5	T1	R
3	55B24LS TA-S	55B24	JIS	12	45	400	238	129	203	227	11.8±1.0	T2	L
4	55B24RS TA-S	55B24	JIS	12	45	400	238	129	203	227	11.8±1.0	T2	R
5	55B24L TA-S	55B24	JIS	12	45	400	238	129	203	227	11.8±1.0	T1	L
6	55B24LSX TA-S	55B24	JIS	12	45	400	238	129	203	227	11.9±1.0	T2	L
7	55D23LX TA-S	55D23	JIS	12	60	500	232	173	204	225	15.4±1.0	T2	L
8	75D23LX TA-S	75D23	JIS	12	65	520	232	173	204	225	15.8±1.0	T2	L
9	55D26LX TA-S	55D26	JIS	12	60	500	260	173	204	225	16.5±1.0	T2	L
10	55D26RX TA-S	55D26	JIS	12	60	500	260	173	204	225	16.5±1.0	T2	R
11	80D26LX TA-S	80D26	JIS	12	70	600	260	173	204	225	17.8±1.0	T2	L
12	80D26RX TA-S	80D26	JIS	12	70	600	260	173	204	225	17.8±1.0	T2	R
13	95D31LX TA-S	95D31	JIS	12	80	660	306	173	204	225	20.1±1.0	T2	L
14	95D31RX TA-S	95D31	JIS	12	80	660	306	173	204	225	20.1±1.0	T2	R
15	105E41R TA-S	105E41	JIS	12	100	720	410	176	213	234	26±1.0	T2	R
16	115E41R TA-S	115E41	JIS	12	120	850	410	176	213	234	27.8±1.0	T2	R
17	31S750 TA-S	G31	SAE	12	90	750	334	176	222	239	24.7±1.0	S	R

STARTER BATTERY-S SERIES													
S/N	Model	International Model	International Standard	Nominal Voltage (V)	Nominal Capacity (Ah)	CCA/-18°C (A)	Dimension				Weight(kg)	Terminal	Layout
							L	W	H	TH			
18	58500 TA-S	58500	SAE	12	48	430	250	174	158	177	12.9±1.0	T2	R
19	85610 TA-S	85610	SAE	12	55	550	230	173	181	203	15.1±1.0	T2	L
20	86610 TA-S	86610	SAE	12	55	550	230	173	181	203	15.1±1.0	T2	R
21	L2-400 TA-S	L2-400	EN	12	60	550	242	175	190	190	15.1±1.0	T2	L
22	L2-400R TA-S	L2-400	EN	12	60	550	242	175	190	190	15.1±1.0	T2	R
23	57220 TA-S	57220	EN	12	72	650	278	175	190	190	18±1.0	T2	L
24	20-82 TA-S	20-82	EN	12	80	680	315	175	190	190	19.9±1.0	T2	L
25	20-100 TA-S	20-100	EN	12	100	750	353	175	190	190	23±1.0	T2	L
26	54565 TA-S	54565	EN	12	45	350	207	175	175	175	11.8±1.0	T2	L
27	54565R TA-S	54565	EN	12	45	350	207	175	175	175	11.8±1.0	T2	R
28	T6 TA-S	T6	EN	12	66	590	278	175	175	175	16.5±1.0	T2	L
29	N120R TA-S	N120	JIS	12	120	780	507	183	194	216	32.5±1.0	T2	R
30	N135R TA-S	N135	JIS	12	135	850	507	183	194	216	33.8±1.0	T2	R
31	N150R TA-S	N150	JIS	12	150	850	510	216	194	217	38.5±1.0	T2	R
32	N150RB TA-S	N150	JIS	12	150	850	510	216	194	229	38.8±1.0	B	R
33	N165R TA-S	N165	JIS	12	165	900	510	216	194	217	40±1.0	T2	R
34	N180R TA-S	N180	JIS	12	180	950	510	216	194	217	41.5±1.0	T2	R
35	N200L TA-S	N200	JIS	12	200	1100	514	267	213	236	50±1.0	T2	L

TAS Series

EFB Start-Stop Battery

TAS Series keeps consistent with JIS and EN standards with super cranking power which ensures dependable start in cold weather, excellent corrosion-resistance performance in high temperature condition and great vibration resistance. The Series has longer life and lower internal resistance, is highly suited for cars, trucks, tractor and the starter for other vehicles as automobile battery.

Product Appearance



PRODUCT FEATURE

- 2 Times Longer Cycle life than SLA Battery
- 1.1 Times Larger CCA than SLA Battery
- Excellent Charging Acceptance
- Excellent Vibration Resistance

CERTIFICATES



APPLICATION

- Car starting
- Ship starting
- Oiler starting

TAS (EFB START-STOP)

S/N	Model	International Model	International Standard	Nominal Voltage (V)	Nominal Capacity (Ah)	CCA/-18°C (A)	Dimension				Terminal	Layout
							L	W	H	TH		
1	Q-85 TAS	Q-85	JIS	12	60	610	232	173	204	225	T2	L
2	Q-85R TAS	Q-85R	JIS	12	60	610	232	173	204	225	T2	R
3	S-95 TAS	S-95	JIS	12	75	660	260	173	204	225	T2	L
4	H5(LN2) TAS	H5(LN2)	EN	12	60	640	242	175	190	190	T2	L
5	H5(LN2)R TAS	H5(LN2)	EN	12	60	640	242	175	190	190	T2	R
6	H6(LN3) TAS	H6(LN3)	EN	12	70	700	278	175	190	190	T2	L
7	H7(LN4) TAS	H7(LN4)	EN	12	80	750	315	175	190	190	T2	L
8	T7(LBN4) TAS	T7(LBN4)	EN	12	75	700	315	175	175	175	T2	L

TAA Series

AGM Start-Stop Battery

TAS Series keeps consistent with EN standards with super cranking power which ensures dependable start in cold weather, excellent corrosion-resistance performance in high temperature condition and great vibration resistance. The Series has longer life and lower internal resistance, is highly suited for cars, trucks, tractor and the starter for other vehicles as automobile battery.

Product Appearance



PRODUCT FEATURE

- 3 Times Longer Cycle life than SLA Battery
- 1.2 Times Larger CCA than SLA Battery
- Excellent Charging Acceptance
- Excellent Vibration Resistance

CERTIFICATES



APPLICATION

- Car starting
- Ship starting
- Oiler starting

TAA (AGM START-STOP)

S/N	Model	International Model	International Standard	Nominal Voltage (V)	Nominal Capacity (Ah)	CCA/-18°C (A)	Dimension /+2mm				Terminal	Layout
							L	W	H	TH		
1	H4(LN1) TAA	H4(LN1)	EN	12	50	570	207	175	190	190	T2	L
2	H5(LN2) TAA	H5(LN2)	EN	12	60	660	242	175	190	190	T2	L
3	H6(LN3) TAA	H6(LN3)	EN	12	70	720	278	175	190	190	T2	L
4	H7(LN4) TAA	H7(LN4)	EN	12	80	800	315	175	190	190	T2	L
5	H8(LN5) TAA	H8(LN5)	EN	12	92	850	353	175	190	190	T2	L
6	H9(LN6) TAA	H9(LN6)	EN	12	105	950	394	175	190	190	T2	L

Cooperation case product

TNC series

Customer M's lead-acid motive TNE series

Customer information:

Customer M is a global electric wheelchair giant;

Background:

the pain points of M customers are:

- 1) At present, the cost of local batteries is high, Customers have demand for cost reduction.
- 2) The low-cost AGM valve-regulated batteries on the market have average cycle performance, and most of them can only be used in the after-sales replacement market;

Product matching:

As a leading enterprise of power batteries, Tianneng can provide products with competitive life and cost



Application	Customized demand	Strong power	Standard IEC60254 SAE/CE/RoHS/UL	Durability Good service life
	Flexible design Battery size is designed according to the space of the battery bin	3 Crate Compatible with high-rate and high-capacity designs, enabling batteries to adapt to high loads and long mileage requirements	Compliance The battery design meets the requirements of the IEC60254 standard Meet the safety requirements of wheelchairs and obtain SAE, CE, RoHS, UL and other certificates	400 ~ 600 The special lead paste formula and rare earth alloy patent technology make the battery have good tolerance, and the cycle life can reach 400 to 600 times, which is suitable for the use of the vehicle body.
Solution				

Highlights:

The cooperation with this customer has increased year by year, and the cooperative manufacturers in this industry have gradually covered other Top wheelchair companies in the world;The total market share of cooperative wheel chair manufacturers accounts for more than 50% of the world.

Cooperation case product

TNC series

Lead carbon TNC series

Background:

In 2010, Tianneng and Harbin Institute of Technology jointly developed lead-carbon super batteries. In 2015, the industrialization of lead-carbon batteries was certified by Zhejiang Province.



In 2019, Tianneng began to sell TNC series lead-carbon batteries overseas. The products are mainly sold to Europe, Australia and America. They are mostly used in new energy base stations, home storage and other application scenarios, and sales have increased rapidly year by year. The growth rate has exceeded 200% for three consecutive years.



CONTACT US NOW!

TIANNENG BATTERY GROUP CO., LTD
TIANNENG INTERNATIONAL CO., LIMITED

 +86-572-6058015

 +86-572-6058015

 info@tianneng.com

 www.tiannengglobal.com

 **HQ Add:**
18#Baoqiao Rd.Huaxi industry park.Changxing.
Zhejiang Province.China

 **INT HQ Add:**
Block C.6/F shun shing plaza, 50 stanley
street, central, Hong Kong

 Tianneng Group Official

 Tianneng Group Official (@GroupTianneng)

 Tianneng Group



Website



Electronic brochure